

## CISCO 100BASE-X SFP FOR FAST ETHERNET SFP PORTS

### PRODUCT OVERVIEW

The Cisco® 100BASE-X Small Form-factor Pluggable (SFP) is a hot-swappable input/output device that plugs into a Fast Ethernet port or slot, linking the port with the network.

Main features include the following:

- Hot-swappable when deployed, the switch or router does not have to reboot.
- Supports the “pay-as-you-populate” model.
- Interchangeable with other 100BASE-X SFPs on the same line card.
- Supports the Cisco quality ID feature that enables the switch or router to identify whether or not the SFP is a Cisco qualified SFP.
- Optically interoperable with respective 100BASE-X Ethernet interfaces on the same link.

**Figure 1.** Cisco 100M Ethernet SFP



### Cisco 100BASE-FX SFP

The Cisco 100BASE-FX SFP (part number GLC-FE-100FX) operates on ordinary multimode fiber-optic (MMF) link spans up to 2 kilometers long.

### Cisco 100BASE-LX10 SFP

The Cisco 100BASE-LX10 SFP (part number GLC-FE-100LX) operates on ordinary single-mode fiber-optic (SMF) link spans up to 10 kilometers long.

### Cisco 100BASE-BX10 SFP

The Cisco 100BASE-BX10 (part numbers GLC-FE-100BX-D and GLC-FE-100BX-U) SFPs operate on ordinary SMF single-strand link spans up to 10 kilometers long.

### TECHNICAL SPECIFICATIONS

#### Platform Support

The Cisco SFPs are supported across a variety of Cisco Systems® switches, routers, and optical transport devices. For more details, refer to the document *Cisco 100M Ethernet SFP Compatibility Matrix*.

## Connectors and Cabling

- Connectors: Dual LC connector (GLC-FE-100FX and GLC-FE-100LX) or single LC connector (GLC-FE-BX-D and GLC-FE-BX-U)

Table 1 provides cabling specifications for the SFPs for installation in a Fast Ethernet SFP port. Note that all SFP ports have LC-type connectors, and the minimum cable distance for all SFPs listed (MMF and SMF [G.652]) is 2 meters [6.5 feet].

**Table 1.** SFP Port Cabling Specifications

SFP	Wavelength (nm)	Fiber Type	Cable Distance
GLC-FE-100FX	1310	MMF	2 km (6562 ft)
GLC-FE-100LX	1310	SMF	10 km (32,810 ft)
GLC-FE-100BX-U	1310	SMF	10 km (32,810 ft)
GLC-FE-100BX-D	1550	SMF	10 km (32,810 ft)

## Standards

- Compatible with IEEE 802.3ah Draft 3.0
- Compatible with standard as specified in IEEE 802.3

Table 2 gives information about fiber loss.

**Table 2.** Fiber-Loss Budgets

SFP	Type	Transmit (dBm)		Receive (dBm)	
		Maximum	Minimum	Maximum	Minimum
GLC-FE-100FX	100BASE-FX	-14	-20	-14	-31
GLC-FE-100LX	100BASE-LX10	-8	-15	-8	-28
GLC-FE-100BX-U	100BASE-BX10-U	-8	-14	-7	-28.2
GLC-FE-100BX-D	100BASE-BX10-D	-8	-14	-7	-28.2

## Dimensions

- Dimensions (H x W x D): 8.5 x 13.4 x 56.5 mm

## Environmental Conditions and Power Requirements

- Operating temperature range: 0 to 50°C (32 to 122°F)
- Storage temperature range: -40 to 85°C (-40 to 185°F)

**Table 3.** Electrical Power Interface

Parameter	Symbol	Minimum	Typical	Maximum	Units
Supply Current	I <sub>s</sub>	–	200	300	mA
Surge Current	I <sup>Surge</sup>	–	–	30	mA
Input Voltage	V <sup>cc</sup>	3.1	3.3	3.5	V

### Warranty

- Standard warranty: 90 days
- Extended warranty (option): Available under a Cisco SMARTnet™ support contract for the Cisco switch or router chassis

### ORDERING INFORMATION

Table 4 gives ordering information for the Cisco SFP.

**Table 4.** Ordering Cisco SFP

Product Number	SFP
GLC-FE-100FX	100BASE-FX SFP for Fast Ethernet SFP ports
GLC-FE-100LX	100BASE-LX10 SFP for Fast Ethernet SFP ports
GLC-FE-100BX-U	100BASE-BX10-U SFP for Fast Ethernet SFP ports
GLC-FE-100BX-D	100BASE-BX10-D SFP for Fast Ethernet SFP ports

### Regulatory and Standards Compliance

#### Safety

- Laser Class 1 21CFR1040

### ADDITIONAL INFORMATION

For more information about Cisco 100BASE-X SFPs for Fast Ethernet SFP ports, contact:

- United States and Canada: 800 553-6387
- Europe: 32 2 778 4242
- Australia: 61 2 9935 4107
- Other: 408 526-7209
- <http://www.cisco.com>